

SPEC SHEE	T 1401-001 E
Section :	1401
Effective :	September 2004
Replaces :	August 2001



# **Screw Compressors for ensilage**

MISTRAL Specialist compressor 365-750 m<sup>3</sup>/h



**TYPHON** Multi-talent compressor 440-1000 m<sup>3</sup>/h





# **Screw compressor - MISTRAL**

# Туре

Oil-free screw compressors for delivery of air absolutely free from any trace of oil or particles.

## Maintenance

Periodic draining (no special oil) No contact between the screws

(no wear)

TYPHON and MISTRAL type screw compressors can be either directly mounted on the chassis using the chassis in different ratios. It can also be driven by hydraulic, electric or heat motor. Easy to use n components. Because of their low speed from 1 200 rpm to 2 000 rpm, many different PTOA can be a

**MISTRAL** The specialist compressor for all construction material ensilage needs with (365 to 750 m<sup>3</sup>/h)

## **Technical characteristics**

### **MISTRAL DIRECT**

Dimensions	
Length (mm)	587
Width (mn)	280
Height (mm)	355
Weight (kg)	108
Inlet flange	NW 80 / Ø 122-4 x M12
Pressure flange	NW 65 / Ø 118-4 x M12



### **MISTRAL INTERCOOLER** - The ultra-light compressor

Dimensions	
Length (mm)	705
Chassis width (mn)	754
Width (mm)	1000
Height (mm)	737
Weight (kg)	275

Subject to technical modifications





# **Applications**

Cereales, granules, flour, lignite, sugar, cement, salt, sand, animal feedstuffs, lime...

# **Materials**

Housings - Gray cast iron, boite and screws - Steel Toothed wheels - Hardened steel, bearing rings - Bronze

PTO shafts and with safety provided by our torque limiter or by a belt-type transmission laterally to nounting kits for lateral mounting on the chassis in cooled use or not are also available in individual used.

# **TYPHON** The multi-talent compressor for all ensilage needs thanks to a 440 to 1000 m<sup>3</sup>/h compressor

# **Technical characteristics**

### **TYPHON DIRECT**

Dimensions	
Length (mm)	709
Width (mn)	360
Height (mm)	350
Weight (kg)	155
Inlet flange	NW 114 / Ø 140-4 x M12
Pressure flange	NW 90 / Ø 125-4 x M12



### TYPHON INTERCOOLER - The multi-talent

Dimensions	
Length (mm)	870
Chassis width (mn)	775
Width (mm)	1028
Height (mm)	690
Weight (kg)	350

Subject to technical modifications





### **Complete solutions for ensilage and tank truck loading**

BLACKMER, part of the DOVER Group, with 2003 turnover of 4.5 billion USD and 26 600 employees, is composed of :

BLACKMER/USA, manufacturing :

vane pumps, pumps and compressors for liquid gas for transportation, liquid gas, industrial and navy (military) markets in North America and with export to Asia, South America and Central America.

#### HAMMOND/UK, manufacturing:

inlet and output rotating compressors, compressed air filters and hydraulic coolers for transportation and industrial markets in Great Britain and Europe,

MOUVEX/F, manufacturing:

all types of volumetric pumps (in particular eccentric piston pumps) and screw compressors

for transportation and industry in the fields of mineral oils, bulk products, foodstuffs, chemistry and pharmaceutical markets in Europe, Africa and the Near East.


BLACKMER offers its customers all over the world complete solutions for all aspects of transporting liquid, gaseous or powdered goods, using appropriate LCC (life cycle cost) based technologies.

For the European market, BLACKMER has localized production facilities for the European market in its plant in Auxerre, France.


We offer a wide range of compressors, pumps and accessories for transporting liquids, mineral oil and gas.

Feel free to contact us for any further detailed information you make wish to have about our products.

### Other drive system possibilities



#### MISTRAL + SAE 5 cast iron flange



Distributed by :		
	World Headquarters 1809 Century Avenue SW Grand Rapids, MI 49503-1530 USA T 616.241.1611 F 616.241.3752	B
Blackmer reserves the right to modify the information and illustrations contained in this document without prior notice.	European Headquarters ZI la Plaine des Isles, rue des Caillottes 89000 Auxerre, FRANCE T +33.3.86.49.87.16 F +33.3.86.49.87.17 contact@blackmar.mouvay.com	D



This is a non-contractual document. 03 Printed in FRANCE by Filigrane